



Type BL
Non-Locating
bearing

Type AL
Non-Locating
bearing

**SOFN Plummer Block for spherical roller bearing with cylindrical bore
(FOR DIRECT MOUNTING)**

AL = CLOSED END, LOOSE BEARING
BL = THROUGH SHAFT, LOOSE BEARING

AF=CLOSED END, FIXED BEARING
BF=THROUGH SHAFT, FIXED BEARING

Bearing Housing Designation	Shaft diameter		dc min	AA	AB	A1	A2	A3	G	Gh	H	H1	H2	J	J1	L	N	N1	S	d1	S1	G1	G2	Ba	Bb	Suitable for Bearing
	da	db																								
SOFN 222	110	108	116	216	229	145	216	13	M24	27	290	160	50	347	75	420	45	28	114.5	120	5	R1/2	R1/2	192	138	22222 CC
SOFN 322	110	108	118	270	290	190	265	20	M30	33	355	190	65	415	100	500	45	35	145	130	8	R1/2	R3/4	243	180	22322 CC
SOFN 224	120	118	126	258	276	170	245	18	M24	27	315	170	55	347	90	420	45	28	138	135	8	R1/2	R1/2	225	164	22224 CC
SOFN 324	120	118	128	285.5	306	190	265	20.5	M30	44	375	200	65	450	115	540	50	35	153	140	8	R1/2	R3/4	254	192	22324 CC
SOFN 226	130	128	138	255	270	180	260	15	M24	32	335	180	60	377	100	450	45	28	135	145	8	R1/2	R1/2	226	164	22226 CC
SOFN 326	130	128	140	300	320	205	285	20	M30	38	405	215	65	470	120	560	50	35	160	150	8	R1/2	R3/4	265	202	22326 CC
SOFN 228	140	138	148	265	280	190	265	15	M30	33	355	190	65	415	100	500	45	35	140	160	8	R1/2	R3/4	234	170	22228 CC
SOFN 328	140	138	150	320	340	220	300	20	M30	42	425	230	80	510	120	630	60	35	170	165	8	R1/2	R3/4	287	215	22328 CC
SOFN 230	150	148	158	265	280	190	265	15	M30	44	375	200	65	450	115	540	50	35	140	170	8	R1/2	R3/4	239	173	22230 CC
SOFN 330	150	148	168	335	350	240	320	15	M30	44	455	245	75	545	150	650	65	35	175	175	10	R1/2	R3/4	292	225	22330 CC
SOFN 232	160	158	168	298	316	205	280	18	M30	38	405	215	65	470	120	560	50	35	158	178	10	R1/2	R3/4	266	193	22232 CC
SOFN 332	160	158	178	350	370	250	335	20	M36	50	480	260	85	590	150	720	70	42	185	190	10	R1/2	R3/4	315	240	22332 CC
SOFN 234	170	168	180	330	350	230	310	20	M30	46	440	235	70	515	130	610	55	35	175	195	10	R1/2	R3/4	290	213	22234 CC
SOFN 334	170	168	188	358	378	260	350	20	M36	44	510	275	85	600	160	730	70	42	189	197	12	R1/2	R3/4	321	244	22334 CC
SOFN 236	180	178	196	340	360	240	320	20	M30	44	455	245	75	545	150	650	65	35	180	205	10	R1/2	R3/4	296	218	22236 CC
SOFN 336	180	178	198	384.5	404	280	370	19.5	M36	48	565	305	95	670	180	820	80	42	202	210	12	R1/2	R3/4	342	260	22336 CC
SOFN 238	190	188	208	350	370	250	335	20	M36	50	480	260	85	590	150	720	70	42	185	220	12	R1/2	R3/4	317	226	22238 CC
SOFN 240	200	198	218	358	378	260	350	20	M36	44	510	275	85	600	160	730	70	42	189	227	12	R1/2	R3/4	315	233	22240 CC
SOFN 244	220	218	238	384.5	404	280	370	19.5	M36	48	565	305	95	670	180	820	80	42	202	255	12	R1/2	R3/4	342	251	22244 CC
SOFN248	240	238	258	400	420	290	380	20	M36	56	625	340	100	740	190	900	80	42	210	270	12	R1/2	R3/4	360	266	22248 CC