



**SOFN Plummer Block for spherical roller bearing with Adapter Sleeve
(FOR DIRECT MOUNTING)**

**AL = CLOSED END , LOOSE BEARING
BL = THROUGH SHAFT, LOOSE BEARING**

**AF=CLOSED END, FIXED BEARING
BF=THROUGH SHAFT, FIXED BEARING**

Bearing Housing Designation	Shaft dia. d	AB	A1	A2	A3	G	Gh	H	H1	H2	J	J1	L	N	N1	S	d1	S1	G1	G2	Bearing Adaptersleeve
SOFN522	100	229	145	216	13	M24	27	290	160	50	347	75	420	45	28	114.5	120	5	R1/2	R1/2	2222CCK H322
SOFN622		290	190	265	20	M30	33	355	190	65	415	100	500	45	35	145	130	8	R1/2	R3/4	2232CCK H2322
SOFN524	110	276	170	245	18	M24	27	315	170	55	347	90	420	45	28	138	135	8	R1/2	R1/2	2224CCK H3124
SOFN624		306	190	265	20.5	M30	44	375	200	65	450	115	540	50	35	153	140	8	R1/2	R3/4	2234CCK H2324
SOFN526	115	270	180	260	15	M24	32	335	180	60	377	100	450	45	28	135	145	8	R1/2	R1/2	2226CCK H3126
SOFN 626		320	205	285	20	M30	38	405	215	65	470	120	560	50	35	160	150	8	R1/2	R3/4	2236CCK H2326
SOFN528	125	280	190	265	15	M30	33	355	190	65	415	100	500	45	35	140	160	8	R1/2	R3/4	2228CCK H3128
SOFN628		340	220	300	20	M30	42	425	230	80	510	120	630	60	35	170	165	8	R1/2	R3/4	2238CCK H2328
SOFN530	135	280	190	265	15	M30	44	375	200	65	450	115	540	50	35	140	170	8	R1/2	R3/4	2230CCK H3130
SOFN630		350	240	320	15	M30	44	455	245	75	545	150	650	65	35	175	175	10	R1/2	R3/4	2230CCK H2330
SOFN532	140	316	205	280	18	M30	38	405	215	65	470	120	560	50	35	158	178	10	R1/2	R3/4	2232CCK H3132
SOFN632		370	250	335	20	M36	50	480	260	85	590	150	720	70	42	185	190	10	R1/2	R3/4	2232CCK H2332
SOFN534	150	350	230	310	20	M30	46	440	235	70	515	130	610	55	35	175	195	10	R1/2	R3/4	2234CCK H3134
SOFN634		378	260	350	20	M36	44	510	275	85	600	160	730	70	42	189	197	12	R1/2	R3/4	2234CCK H2334
SOFN536	160	360	240	320	20	M30	44	455	245	75	545	150	650	65	35	180	205	10	R1/2	R3/4	2236CCK H3136
SOFN636		404	280	370	19.5	M36	48	565	305	95	670	180	820	80	42	202	210	12	R1/2	R3/4	2236CCK H2336
SOFN538	170	370	250	335	20	M36	50	480	260	85	590	150	720	70	42	185	220	12	R1/2	R3/4	2238CCK H3138
SOFN540	180	378	260	350	20	M36	44	510	275	85	600	160	730	70	42	189	227	12	R1/2	R3/4	2240CCK H3140
SOFN544	200	404	280	370	19.5	M36	48	565	305	95	670	180	820	80	42	202	255	12	R1/2	R3/4	2244CCK H3144
SOFN 548	220	420	290	380	20	M36	56	625	340	100	740	190	900	80	42	210	270	12	R1/2	R3/4	2248CCK H3148